

Goslyn™ Grease Recovery Devices



Leaders in Restaurant Grease Recovery

An innovative replacement to conventional grease traps and/or grease interceptors. Automated Grease Recovery Devices (GRD) that outperform and outlast all grease traps, grease interceptors, and grease removal devices on the market.

Grease Trap Pumping Eliminated



*Grease Blockages
Grease Trap Chemicals &
Grease Trap Odours
are History*

*Recovered Grease
is Recyclable with
Zero Waste*



Goslyn Ontario

647 763 4060

www.greasetrap.ca

Goslyn™ Grease Recovery Devices



99.6% Grease Recovery

Goslyn Grease Recovery Devices recover fats, oils, grease (FOG) and food solids from foodservice wastewater. The recovered grease is recycled with the waste vegetable oil (WVO) from the deep-fryers.

The recovered grease is collected in an opaque cassette located at the front of the unit. The recovered grease is clearly visible.



Goslyn Devices are made of rust and leak resistance stainless steel. Goslyn does not have moving mechanical parts providing a long, productive, and durable life.

Grease recovery is 99.6% from restaurant wastewater. Goslyn exceeds grease recovery requirements in any jurisdiction.



Goslyn conveniently fits under or near any 2 or 3 compartment sink. Goslyn attaches to automatic dishwashers and 3-compartment sinks simultaneously. Goslyn units are installed flush to the floor. Excavation or concrete cutting is not required on new or retrofit installations.



Unlike conventional grease traps and interceptors Goslyn traps all food solids to 1/16th of an inch. The solids strainer basket is located under the top cover for easy and clean maintenance. Goslyn requires 2 minutes maintenance daily.



Glenn Martin

647 763 4060

Goslyn™ Grease Recovery Devices



Goslyn Commercial & Industrial Models

Grease Recovery Device Specifications

Goslyn Model	Gallons Per Minute	Height	Length	Width	Height to Inlet Centre	Height to Outlet Centre
--------------	--------------------	--------	--------	-------	------------------------	-------------------------



Grease Recovery Models - Restaurant Kitchens - Grocery

GOS 40	10US	16.0"	24.0"	16.0"	12.4"	10.5"
GOS 80	25US	20.5"	37.0"	24.0"	14.8"	12.4"
GOS 60LP	15US	14.0"	36.0"	16.0"	10.0"	6.7"
GOS 80LP	25US	14.0"	40.0"	24.0"	14.8"	10.0"



LP = Low Profile Units

Grease Recovery Models - Industrial - Food Manufacturing

GOS 160	50US	21.0"	39.0"	24.0"	15.0"	13.0"
GOS 240	75US	27.0"	40.0"	24.0"	20.0"	16.0"
GOS 320	100US	31.0"	42.0"	24.0"	24.0"	21.0"



GOS-40 = 10 US GPM - Unit Weight 84 Lbs

GOS-60 = 15 US GPM - Unit Weight 117 Lbs

GOS-80 = 25 US GPM - Unit Weight 130 Lbs

GOS-160 = 50 US GPM - Unit Weight 217 Lbs

GOS-240 = 75 US GPM - Unit Weight 280 Lbs

GOS-320 = 100 US GPM - Unit Weight 351 Lbs

Goslyn Electrical and Material Specifications

Standard GFI 3 Prong Plug - 110 Volt, 1000 watts, 9 Amps

Exterior Construction - 2.5mm 308 Stainless Steel

Goslyn Ontario 647 763 4060

www.greasetrap.ca

Goslyn™ Grease Recovery Devices



Fully Canadian Certified

